

L61XX

86

MATERIAL SAFETY DATA SHEET
FOR COATINGS, RESINS AND RELATED MATERIALS
 (Approved by U.S. Department of Labor 'Essentially Similar' to for OSHA-20)

MANUFACTURER'S NAME
THE SHERWIN-WILLIAMS COMPANY
 101 Prospect Avenue N.W.
 Cleveland, Ohio 44115
 DATE OF PREPARATION
 13-Nov-86

EMERGENCY TELEPHONE NO.
 (216) 566-2917
 INFORMATION TELEPHONE NO.
 (216) 566-2902

Section I -- PRODUCT IDENTIFICATION

PRODUCT NAME
OPEX* Production Lacquer, Non-Lead Colors
 PRODUCT NUMBERS AND COLORS
 L61 A 23 Pale Gray
 L61 B 21 Black
 L61 G 33 Dark Green
 L61 L 30 Light Blue
 L61 L 31 Rich Blue
 L61 L 32 Blue
 L61 N 17 Brown
 L61 R 44 Red
 L61 W 19 Tinting White
 L61 W 34 White
 L61 W 40 Semi-Gloss White
 L61 W 100 White
 L61 Y 36 Yellow
 L65 F 1 Flattening Agent
 T82 C 100 Mixing Lacquer, Clear

--- Including Non-Lead Containing Custom Colors ---

PRODUCT CLASS
 Alkyd-Cellulose Nitrate Lacquer

Section II -- HAZARDOUS INGREDIENTS

CAS NO.	INGREDIENT	% by WEIGHT	ACGIH-TLV	OSHA-PEL	UNITS	V.P.
64742-89-8	Lt. Aliphatic Hydrocarbon Solvent.	5-10	100	500	PPM	53.0
64742-48-9	V. M. & P. Naphtha.	5-10	300		PPM	12.0
108-88-3	Toluene.	5-10	100	200	PPM	22.0
1330-20-7	Xylene.	<5	100	100	PPM	5.9
64-17-5	Ethanol	0-5	1000	1000	PPM	44.0
67-63-0	2-Propanol	<5	400	400	PPM	33.0
78-83-1	2-Methyl-1-propanol	10	50	100	PPM	8.7
111-76-2	2-Butoxyethanol	<5	25	50	PPM	0.6
78-93-3	Methyl Ethyl Ketone.	5	200	200	PPM	70.0
110-19-0	Isobutyl Acetate.	10-20	150	150	PPM	12.5
117-81-7	Bis(2-ethylhexyl) Phthalate. <IND>	0-5	5		Mg/M3	
13463-67-7	Titanium Dioxide.	0-15	10		Mg/M3	

< > Ingredient is an IARC<1>, NTP<ND> or OSHA<C> listed carcinogen

Section III -- PHYSICAL DATA

EVAPORATION RATE -- Slower than Ether	VAPOR DENSITY -- Heavier than Air
BOILING RANGE (F) 172 - 340	% VOLATILE VOLUME 65-75

Section IV -- FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION
 RED LABEL -- Flammable, Flash below 100 F
 EXTINGUISHING MEDIA
 Carbon Dioxide, Dry Chemical, Foam

Continued on page 2

L61XX

OPEX* Production Lacquer, Non-Lead Colors

page 2

UNUSUAL FIRE AND EXPLOSION HAZARDS

Keep containers tightly closed. Isolate from heat, electrical equipment, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Section V -- HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE -- See Section II
 EFFECTS OF OVEREXPOSURE

ACUTE: Overexposure causes eye, skin and respiratory irritation. May cause nervous system depression accompanied by headache, dizziness, nausea, confusion and staggering gait. Extreme overexposure may result in unconsciousness and possibly death.
 CHRONIC: Bis(2-ethylhexyl) Phthalate has been shown to cause liver tumors in rats and mice fed high levels over a long period of time, but not at lower levels. It poses little risk to man at the low exposure typical in product use. Prolonged overexposure to ingredients in Section II may cause adverse effects to the liver, urinary, blood forming, cardio-vascular, and reproductive systems. Rats exposed to titanium dioxide dust at 250 mg./m3 developed lung cancer, however, such exposure levels are not attainable in the workplace. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

EMERGENCY AND FIRST AID PROCEDURES

If INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet.
 If on SKIN: Wash affected area thoroughly with soap and water.
 Remove contaminated clothing and launder before re-use.
 If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.

Section VI -- REACTIVITY DATA

STABILITY -- Stable
 HAZARDOUS DECOMPOSITION PRODUCTS
 By fire: Carbon Dioxide, Carbon Monoxide
 HAZARDOUS POLYMERIZATION -- Will Not Occur

Section VII -- SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
 Remove all sources of ignition. Ventilate and remove with inert absorbent.
 WASTE DISPOSAL METHOD
 Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.
 Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

Section VIII -- PROTECTION INFORMATION

PRECAUTIONS TO BE TAKEN IN USE
 Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.
 Protect against dust which may be generated by sanding or abrading the dried film.

Continued on page 3

L61XX OPEX* Production Lacquer, Non-Lead Colors

page 3

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section II is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear respiratory device approved by NIOSH/MSHA for protection against materials in Section II.

PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section II.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

Section IX -- PRECAUTIONS

DO NOT STORAGE CATEGORY -- 1B

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Contents are FLAMMABLE. Keep away from heat, sparks, and open flame.
 During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

OTHER PRECAUTIONS

This coating contains materials classified as nuisance particulates, for example titanium dioxide, calcium carbonate, etc. (see ACGIH TLV List, Preface and Appendix D), which may be present at hazardous levels only during sanding or abrading of the dried film.

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

HMIS

HEALTH	2*
FLAMMABILITY	3
REACTIVITY	0

MSDS for L61XL
Lead-Containing Colors
on reverse.

This Material Safety Data Sheet conforms to the Hazard Communication standard, 29 CFR 1910.1200(g)(4), for similar complex mixtures.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.